

## **Klemsan<sup>®</sup>**

## 270814 KPR-SCE-24VDC-1C

1 C/0 PLC Relay

Input	Nominal Voltage (Un)	24VDC	
	Operating Voltage Range	(0.8 - 1.15) x Un	
	Release Voltage	0.2 x Un	
	Integrated RCZ Filter —		
Power Consumption	AC	_	
	DC	<0.2W	
Contact Characteristic	Туре	1 C/O (SPDT)	
	Material	AgSnO2	
	Coil Voltage	24VDC	
	Coil Empedance	3390(1±15%)Ω	
	Coil Consumption	170mW	
	Operate Time	Maks. 10ms	
	Release Time	Maks. 5ms	
	Max. Ratings - AC	6A/250VAC;1500VA	
	Max. Ratings - DC	6A/30VDC;180W	
Mechanical Lifetime	NO	≥ 10 <sup>7</sup> operations	
Electrical Lifetime Operations (UL approval, 85°C)	NO	3x10 <sup>4</sup> operations	
	NC	1x10 <sup>4</sup> operations	
Dielectic Strength	Between Relay Coil and Contacts	4000VAC 1 min.	
	Between Contacts	1000VAC 1 min.	
Ambient Conditions	Operating Temperature	-40°C +85°C	

	Storing Temperature	-40°C +85°C
	Relative Humidity (No Condensation)	5% - 85%
Certificates	UL508, IEC EN 61984-2011, IEC EN 61947-1:2010	_
Socket	Туре	KPR-SCE-24VDC-1C (RELAY SOCKET),KPR-SCE-24VDC-1C (RELAY SOCKET),KPR-SCE-24VDC-1C (RELAY SOCKET),KPR-SCE- 24VDC-1C (RELAY SOCKET),KPR-SCE-24VDC-1C (RELAY SOCKET),KPR-SCE-24VDC-1C (RELAY SOCKET),KPR-SCE-24VDC-1C (RELAY SOCKET),KPR-SCE-24VDC-1C (RELAY SOCKET)
	Definition	PLC RELAY SOCKET (24VDC),PLC RELAY SOCKET (24VDC),PLC RELAY SOCKET (24VDC),PLC RELAY SOCKET (24VDC),PLC RELAY SOCKET (24VDC),PLC RELAY SOCKET (24VDC),PLC RELAY SOCKET (24VDC),PLC RELAY SOCKET (24VDC)
	Order Number	270 815,270 815,270 815,270 815,270 815,270 815,270 815,270 815
	Packing Units	10,10,10,10,10,10,10
Relay	Туре	Slim Type 24VDC Relay
	Definition	Relay for 270 814 and 270 815
	Order Number	095 041
	Packing Units	10 pcs.
Plug-In Bridge 16	Туре	TK-KPR-S (KPR-SCE BRIDGE/16)
	Definition	Plug - in bridge for 16 hole
	Order Number	476 605
	Packing Units	25 pcs.
Plug-In Bridge 8	Туре	TK-KPR-S (KPR-SCE BRIDGE/8)
	Definition	Plug in bridge - 8
	Order Number	476 606
	Packing Units	50 pcs.
Plug-In Bridge 2	Definition	_
	Order Number	_
	Quantity	
	Туре	_
Dekafix	Туре	DG 10/6T
	Definition	Terminals Lebels for interface relays
	Order Number	505 390
	Packing Units	360

## Order Info

270814 1 C/0 PLC Relay

© 2019 Klemsan A.Ş. www.klemsan.com